



DRAKE PNEUMATICS
Air Tool Repairs & Industry Supplies



Parker Semi Rigid Nylon & Flexible Polyurethane Tubing *In Stock*



- Nylon 3mm OD to 16mm OD
- Polyurethane 3mm OD to 14mm OD
- Clear, Black, Green, Red, Blue, Yellow, Grey
- 25m Boxed Coils
- Convenient Tubepack® packaging
- **See Catalogue Section 1, page 38-41**

Polyurethane Tubing Specification:

- Vacuum Capacity: 755mm Hg (99% Vacuum)
- Large range of working temperatures and pressures
- High flexibility and small bend radius
- Negligible pressure drop
- Consistent rigidity, good ageing
- UV resistant
- Silicon free
- Excellent resistance to vibration
- Shore hardness 52D, conforms to NF E49-101 standard

Nylon Tubing Specification:

- Vacuum Capacity: 755mm Hg (99% Vacuum)
- Large range of working temperatures and pressures
- Good chemical resistance
- Negligible pressure drop
- Consistent rigidity, good ageing with constant tolerance on O.D.
- Strong abrasion resistance
- Silicon free
- Shore hardness 60°D

Order Online www.drakepneumatics.co.uk

If you need a webshop registration please contact us

- **Orders over £300 nett FREE next day delivery**
- **Only £7.50 next day delivery for orders below £300 nett when ordered online @ www.drakepneumatics.co.uk**

**Carriage charges quoted are applicable to UK Mainland only for other areas please contact us*

Drake Pneumatics
138 Oyster Lane, Byfleet, Surrey, KT14 7JQ
T: 01932 355239 F: 01932 354954
E: sales@drakepneumatics.co.uk